



ArmorPoxy Inc.  
1260 North Ave  
Plainfield, NJ 07062  
[armorpoxy.com](http://armorpoxy.com)  
E: [info@armorpoxy.com](mailto:info@armorpoxy.com)  
P: 888-755-7361

# ARMRNWSM

## ARMOR RENEW WOOD AND CONCRETE RESURFACER - SMOOTH

### PRODUCT DESCRIPTION

Armor Renew is a water-based polyurethane modified acrylic coating designed to resurface wood decks, docks, concrete patios and walkways. Armor Renew Smooth has excellent weather resistance to extend the life of deck and patio surfaces.

**DECKS:** For wood and most composite decks. Follow specific manufacturer's recommendation before applying to any composite decking.

**CONCRETE:** For use on broom swept or porous concrete surfaces. Do not use on smooth or floated concrete, fiberglass, tile or metal surfaces.

**FOR EXTERIOR USE ONLY**

### PRODUCT FEATURES

- Ideal for worn decks, steps, uprights, and patios
- 1 coat system for upright surfaces
- 2 coat system for horizontal surfaces
- Excellent weather resistance
- Ready for use in 24 hours
- Algae and mildew resistant coating
- Available in 30 different colors, *must be tinted before use*
- Can be applied using a ¾" nap roller, a short nap stain pad or a synthetic paint brush.

### PRODUCTS TO BE USED WITH

- Renew Deck Cleaner
- Renew Wood Deck Primer
- Flash Bond Primer (for Trex type) decking

### PHYSICAL PROPERTIES

Resin Type	Water-based Acrylic blended with Polyurethane
Pigment Type	Titanium Dioxide and Inert Pigment
Solvents	Glycol Ethers, Water
Weight-Per Gallon	9.7 lbs
Weight-Per Liter	1.16 kg
Solids By Weight	43.9%
Solids By Volume	34.6%
Volatile Organic Compounds	<100 g/l (0.83lbs./gal.)
Recommended Dry Film Thickness(DFT)/Coat	2 mils
Practical Coverage (assume 15% material loss)	Approximately 250 sq.ft./gal
Dry Times (@ 70-80°F (21-27°C) and 50% RH	Rates will vary based on surface profile
Touch	---
Light Traffic	2-4 hours
Replace Furniture	24 hours
Full Cure	24 hours
Shelf Life	7 days
Flash Point	3 years
Storage	>200°F (93°C)
Safety Information	Protect from freezing. For additional information, see the SDS

### BENEFITS



Ready for Use  
in 24 Hours




Available in  
over 30 Colors



Roll On  
Application



Weather  
Proof



Algae and Mildew  
Resistant

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.